

Lashing strap ProSafe ratchet 1.5 m, 400 daN

Material no.: 1000012322 | Matchcode: PSH RA 1,5 | EAN code: 4045294769284



- » integrated clamp for loose end
- » strap width of 25 mm
- » quicker access to freight
- » universally applicable in vehicles
- » enables flexible load securing

Materials & Color

Material:	PA6 Polyester Steel
Color:	Anthracite

Dimensions

External dimensions:	61.3 x 2.5 x 1.4 in
Length in inch:	1500








Technical data

Weight:	0.93 lb
Maximum tensile force in daN:	400

Lashing strap ProSafe ratchet 1.5 m, 400 daN

Material no.: 1000012322 | Matchcode: PSH RA 1,5 | EAN code: 4045294769284

Accessories

	Material no.	Description	Matchcode	EAN code
	1000001736	ProSafe individual lashing point restraint pole	EZ S PS	4045294228040
	1000001870	Flexible edge protection lash.straps(4x)	ZFKS ZG VPE4	4045294230999
	1000003736	ProSafe CargoStopp	CST PS	4045294403072
	6000001231	ProSafe individual lashing point	EZ PS	4045294224646
	6000001259	ProSafe floor lashing point	BZ PS S	4045294225179
	6000001260	ProSafe floor lashing point restraint pole	BZ SP PS	4045294225186
	6000001116	Anti-rattle mat 750x500	ARM 750X500	4045294239565

Lashing strap ProSafe ratchet 1.5 m, 400 daN

Material no.: 1000012322 | Matchcode: PSH RA 1,5 | EAN code: 4045294769284

Description

The ProSafe lashing strap with a ratchet and a length of 1.5 m can be universally used in the vehicle and in connection with the Sortimo TopSystem on the vehicle roof. The ratchet enables a higher clamping force to be achieved as would be possible with the clamping lock. This means you can secure particularly heavy objects professionally and quickly. The lashing strap is compatible with ProSafe uprights from the Sortimo Globelyst van racking system, ProSafe rails, SoboGrip ProSafe floors, single lashing points, restraint poles with single lashing points as well as with the original lashing points from the vehicle manufacturer. The lashing strap has a resilience of up to 400 daN and a width of 25 mm. The lashing strap also has a clamping function for the loose end. The clamping lever attached to the ratchet in a space-saving manner can be used to fasten the remaining end in place quickly and easily, thus preventing irritating noises while driving. When used in the vehicle, it also prevents dangerous trip hazards. The anti-rattle mat (Art. No.: 6000003365) can be cut to size and prevents the load from shifting. An edge protection profile should be used to protect the lashing strap and the load.

We reserve the right to make changes in the interest of technical progress, as well as correcting printing errors and mistakes. Pictures are similar, decorative material not included. With the publication of this data sheet, previous editions lose their validity. Version: 29.02.2024